

# DECLARATION OF PERFORMANCE

DE0001/02



Unique identification code of the product-type:

**PCI Carraflex® (DE0001/02)**

Intended use/es:

**EN 12004 C2FT S1**

**Improved fast setting deformable cementitious adhesive with reduced slip for tiles for indoor and outdoor use**

Manufacturer:

**PCI Augsburg GmbH, Piccardstraße 11, D-86159 Augsburg**

System/s of AVCP:

**System 3, System 3 (Reaction to fire)**

Harmonised standard / Notified body/ies:

**EN 12004:2007+A1:2012**

**Technische Universität München Materialprüfungsamt für das Bauwesen (NB 1211)  
MPA Dresden GmbH (NB 0767)**

Declared performance/s:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class A2-s1,d0; A2fl-s1	System 3	EN 12004:2007+A1:2012
Early tensile adhesion strength	≥ 0,5 N/mm <sup>2</sup>	System 3	
Initial tensile adhesion strength	≥ 1,0 N/mm <sup>2</sup>		
Tensile adhesion strength after water immersion	≥ 1,0 N/mm <sup>2</sup>		
Tensile adhesion strength after heat ageing	≥ 1,0 N/mm <sup>2</sup>		
Tensile adhesion strength after freeze/thaw cycle	≥ 1,0 N/mm <sup>2</sup>		
Dangerous substances	NPD		

The performance of the product identified above is in conformity with the set of declared performance/s.

This declaration of performance is issued, in accordance with Regulations (EU) No 305/2011 and No 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:  
Augsburg, 02.11.2020

.....  
Marc C. Köppe  
managing director

.....  
Frank Rösiger  
managing director